

Wechselrichter Marke	Wechselrichter Typ		Wechselrichter Eigenschaften			Komm- unikation*	Firmware Version
			Spannungs- bereich [V]	max. Strom [A]	nutzb. Energie		
Victron Energy	Multiplus 48V (II + GX)	Batterie, 1-phasig, On-/Off-Grid, Backup Power	38-66V	200A	89%	CAN	422/V2.15
	Quattro 48V			120A			
	Easy Solar 48V (II + GX)	100A					
	Multi RS Solar	Hybrid, 1-phasig, On-Grid, Backup Power	36-60 V	70A	92%		
SMA Solar Technology AG	SI 4.4-M	Batterie, 1+3-phasig On-/Off-Grid	41-63V	75A	80%	CAN	n.v.
	SI 6.0-H			110A			
	SI 8.0-H			140A			
	SI 6048US			110A			
Goodwe	GW-BP	Batterie, 1+3-phasig On-Grid, Backup Power	40-60V	75-100A	84%	CAN	n.v.
	EM	Hybrid, 1-phasig, On-/Off-Grid		50A			
Sofar	ME3000SP	Batterie, 1-phasig, On-Grid, Backup Power	42-58V	70A	71%	RS485 (115200) / CAN	V1.2
	HYD series	Hybrid, 1-phasig, On-/Off-Grid		75-100 A			
Sermatec	SMT-5K-TL-LV	Hybrid, 1-phasig, On-Grid	40-58V	70 / 100A	84%	RS485(9600)/ CAN	n.v.

R2 Natrium-Ionen Niedervolt-Batteriemodul - Kompatible Wechselrichter

Wechselrichter Marke	Wechselrichter Typ		Wechselrichter Eigenschaften			Kommunikation*	Firmware Version
			Spannungsbereich [V]	max. Strom [A]	nutzb. Energie		
Solis	RHI series	Hybrid, 1-phasig, On-/Off-Grid, Backup Power	42-58V	62.5-100 A	71%	CAN	90009
	RAI series	Batterie, 1-phasig, On-/Off-Grid, Backup Power	40-60V	60A	84%		
	S6-EH1P(3-8)K-L-PLUS	Hybrid, 3-phasig, On-/Off-Grid, Backup Power	40-60V	190A	84%		
Deye	SUN-SG01LP1 series	Hybrid, 1-phasig, On-Grid	40-60V	250	84%	CAN	V1586
	SUN-SG03LP1 series			90-130 A			
	SUN-SG04LP3 series	Hybrid, 3-phasig, On-Grid		240			
	SUN-SG05LP3 series						
Delios s.r.l.	DLS/C series	Hybrid, 1-phasig, On-Grid	40-65V	50A	84%	CAN	A 1.30; B 1.18; C1.27
	DLS AC series	Batterie, 1-phasig, On-Grid		50-100 A			
SolarMax	ES series	Batterie, 1-phasig, On-Grid	40-65 V	35-100 A	84%	CAN	A 1.30; B 1.18; C1.27
	AC series						
Growatt	SPH3000 - 6000	Hybrid, 1-phasig, On-Grid	42-59V	35-100 A	71%	CAN	RA1.0
Senergy	SE 4K6/5K/6KHB-60/120	Hybrid, 1-phasig, On-/Off-Grid, Backup Power	40-65V	120A/120A	84%	RS485(9600)	0.6.0
FSP Power Solution	PowerManager Hybrid series 4-15kW	Hybrid, 1-phasig, On-Grid	40-60V	5-300 A	84%	RS485(9600)	V1.00 V2.61

R2 Natrium-Ionen Niedervolt-Batteriemodul - Kompatible Wechselrichter

Wechselrichter Marke	Wechselrichter Typ		Wechselrichter Eigenschaften			Kommunikation*	Firmware Version
			Spannungsbereich [V]	max. Strom [A]	nutzb. Energie		
Hoy miles	HYS-LV Series	Hybrid, 1-phasig, On-/Off-Grid, Backup Power	40-60V	75 - 100A	84%	CAN	Power - ab V01.04.19 Safety - ab V01.02.13 System - ab V00.02.18
	HAS-LV Series	Batterie, 1-phasig, On-/Off-Grid		80 - 200A			
LEDIT	FVDi series	Hybrid, 1,-phasig, On-Grid	40-65V	100A	84%	CAN	A 1.30; B 1.18; C1.27
GMDE	SolDate 3700TL+BM024	Hybrid, 1-phasig, On-/Off-Grid, Backup Power	40-58 V	50A	84%	RS485(9600)	V2.0.1

* Die Kommunikation findet über das Pylontech Protokoll statt

n.v.: Informationen nicht verfügbar

Die Daten beziehen sich auf die Herstellerangaben. Salzstrom übernimmt keine Haftung für die Richtigkeit und/oder Vollständigkeit der Angaben.